

Version: May 7, 2024

MINI COATING PUMP

Extend the life of pipes with the Picote Brush Coating ™ System



The Picote Brush Coating™ system is a simple, fast, and practical coating solution used to renovate and prolong the life of stack pipes, drains, sewers, water pipes*, electrical conduits, and more.

Clean the pipe well and apply two coats for a corrosion barrier. Alternatively, apply additional coats of resin to form a new, seamless semi-structural rehabilitation that should last 30-50 years.*

Can be combined with several different Miller models to meet project needs based on pipe length & diameter.

For pipe coating and degreasing in DN32-200 (11/4-8") diameter pipes up to 22m (75') in length.

USES AND BENEFITS

- Controls the flow of Picote Brush Coating™ DC1000E, Dual Color Epoxy Resin.
- Adjustable pump speed & direction.
- Hand-held locking operator control trigger. When the button is pushed the pump is engaged and will operate until pressed again.
- Combine and secure the Mini Coating Pump to the Mini Miller, Mini Cleaner, or Super Battery Mini Miller/Mini Cleaner frames for a portable compact system.
- Can also be used to remove fats, oils, and grease from pipes by pumping degreaser down the line to assist with cleaning.
- Includes Resin Cup Package, 3x Hose Connectors, Hose Clamps and 2x Brush Stoppers.
- *NSF61 Certified for DN100 (4") and larger pipes (final coat in white).

Technical Specifications	
Pipe Diameters	DN32-200 (11/4-8")
Max Range	22m (75')
Power	UK/US: 110V, 15 Amp EU: 220V, 16 Amp
Output (kw)	0.18
Weight	16kg (35.5 lbs)
Size	41x42x54.4 cm
	16.2x16.5x21.5"



Optional Picote Heater

Decrease time between coats by 30%. Includes 5m (16.4') Heater Hose.

Air outlet temperature is limited to +55° C (131°F). Automatic thermal cut-out in both motor and heating element.











Version: May , 2024

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Picote Mini Coating Pump Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS & SPARE PARTS

Products & Spart Parts	
PN	Description
2220100002	Mini Coating Pump US 110v
1350000024US	Picote Heater US 110v
2130001001	Smart Mixer 2.0 US 110v
2220100001	Mini Coating Pump EU 230v
1350000024	Picote Heater EU 230v
2130001001EU	Smart Mixer 2.0 EU 230v
2220100005	Mini Coating Pump UK 110v
	Picote Heater UK 110v
2130001001UK	Smart Mixer 2.0 UK 110v
2220200004	Coating Resin Cup Package - 10 Pieces
2220100004	Pump Hose: 25m (82') Package
2220100011	Pump Hose: Pre-cut to 24cm (9.4") / 50pc Package
2220100003	Delivery Hose: 25m (82') Package
2220100009	Delivery Hose: 200m (656') Package
2220100007	Hose Connector with Hose Clamps (10 & 13mm)
9500000382	Hose Clamp (10mm)
9500000381	Hose Clamp (13mm)
900000338	Brush Stopper 8mm (1/3")
2110000003	Delivery Hose Lube: 0.95L (1 Quart)
Brushes for 6mm (1/4") Shaft	
2120000037	Coating Brush DN40 (1½") for DN32 (1¼") Pipe
Brushes for 8mm (1/3") shaft	
2120000050	Coating Brush DN50 (2") for DN32 (1¼") Pipe
2120000075	Coating Brush DN75 (3") for DN50 (2") Pipe
2120000100	Coating Brush DN100 (4") for DN70 (3") Pipe
2120000125	Coating Brush DN125 (5") for DN100 (4") Pipe
2120000175	Coating Brush DN175 (6.9") for DN150 (6") Pipe
2120000220	Coating Brush DN220 (8.7") for DN200 (8") Pipe







