



# PICOTE MINI MILLER +C / MINI CLEANER +C

*Millers with Integrated Cameras*



The Picote Mini Miller +C and Mini Cleaner +C units feature an integrated 30m (98') color camera that makes viewing of cleaning and cutting jobs easier and helps to make Picote Brush Coating™ setup even simpler.

The Mini Miller +C's color, self-leveling camera head has a 512hz integrated sonde while the Mini Cleaner +C features a smaller color camera head that allows it to follow the Mini Cleaner through DN50 (2") P-traps & bends.

Please see product fact sheets for the Mini Miller or Mini Cleaners for specifications and additional product information.

## USES AND BENEFITS

- Onboard camera system makes for convenient viewing of cleaning, cutting, & coating jobs
- Waterproof\* protective camera case with handle
- Digital footage counter
- On screen time & date display
- Stainless steel camera heads (IP68 class)
- Video and snapshot capture modes
- LED camera lights with brightness control
- Also available as an upgrade package for standard Battery Powered Mini Cleaners & Mini Millers
- You can use both hands on the shaft due to the operator presence foot control pedal that is standard on all Picote Millers

\* When case is latched and closed.

Technical Specifications	
Camera Cable	30m (98')
Recording	SD Card (32GB Max)
Camera Power	Battery with 12V charger
Battery Life	Up to 8 hours
Miller Power	UK/US: 110/120V, 15 Amp EU: 220/230V, 16 Amp
Lighting	LEDs with brightness control
Capture Options	Video and snapshot
Screen Size	17.8cm (7") color monitor
Mini Miller +C Camera	
2 Camera Heads	23mm (7/8"), color, self leveling 23mm (7/8"), color
Locating	512 hz integrated sonde
Lighting	12 LEDs with brightness control
Vision Angle	120°
Weight	31½ kg (69½ lbs)
Mini Cleaner +C Camera	
Camera Head	14mm (9/16"), color
Locating	512 hz integrated sonde
Lighting	8 LEDs with brightness control
Vision Angle	82°
Weight	31kg (69 lbs)

## More Info/Guides/Technical Support:

- Visit [picoteinstitute.com](http://picoteinstitute.com) for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Mini Cleaner +C and Mini Miller C+ Operation & Safety Manuals or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

## PRODUCTS AND SPARE PARTS

Mini Cleaner +C / Mini Miller +C Product List	
PN	Description
3540001817	Mini Miller +C EU, 230v
3540001817UK	Mini Miller +C UK, 110v
3540001817US	Mini Miller +C US, 110v
3540001816	Mini Cleaner +C EU, 230v (with cleaning package)
3540001816UK	Mini Cleaner +C UK, 110v (with cleaning package)
3540001816US	Mini Cleaner +C US, 110v (with cutting package)
3540001818US	Mini Cleaner +C US, 110v (with cleaning package)
Spare Parts	
PN	Description
900001754	Mini Miller +C Camera Head, 23mm (7/8"), sonde, color, self leveling
900001752	Mini Miller +C Camera Head, 23 mm (9/16"), sonde, color
900001760	Mini Cleaner +C Camera Head, 14mm (9/16"), sonde, color
1312030085017	Mini Miller - 8mm (1/3") Shaft with Thick Casing 17.4m (57')
9331008000	Thick outer casing for 8mm (1/3") shaft
900000856	Micro/Mini Miller Safety Clutch
900000920	Mini Miller Silicone Spring 5pcs, spare part
9530000041	Safety Clutch Upgrade Kit for Micro/Mini Miller
9530000134	Strain Relief Micro/Mini Miller
9530000134-1	Strain Relief Spring Micro/Mini Miller for Safety Clutch
131203108517	Mini Cleaner Replacement Shaft with Spring Casing 16m (52')
9311713099	Mini Cleaner Shaft Spring Casing only 16.5m (54')
900001204	Mini Cleaner Safety Clutch
900001205	Silicon Spring (red) 5pcs for Mini Cleaner, spare part
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant package (6 bottles)
9530000045	Micro/Mini Miller/Mini Cleaner Handle Upgrade Kit