

# BATTERY SUPER MINI CLEANER

*Flexible, Efficient, Mobile, & Eco-Friendly*



The Picote Mini Cleaner was specially designed for plumbers working in smaller diameter pipes. Thanks to its highly flexible 8mm shaft, working in DN32-75 pipes is extremely easy, even those with multiple 90° bends and p-traps as small as DN50.

While the new Battery Super Mini Cleaner does run off a long-lasting battery, it's much more than just a battery-powered version of its predecessor. It is loaded with new features like an electronic clutch, stepless speed control, and a dedicated motor to make it even more powerful, mobile, & eco-friendly.

In the UK, and other countries with non-syphonic toilets, it can also be pushed through the toilet and into a stack pipe for cleaning without having to remove the toilet.

## USES AND BENEFITS

- **Flexible Shaft:** Navigates multiple 90°s & DN50 P-traps.
- **High Speed/High Torque:** 550-2200 RPM.
- **Dedicated Motor:** Optimized for increased power matched with better clutch engagement precision to create perfectly balanced performance.
- **Stepless Speed Control:** Seamless speed adjustment whether you need raw power for stubborn blockages or finesse for delicate operations, control is at your fingertips.
- **Electronic Clutch:** Automatically disengages the drive if you encounter resistance beyond its set limit. It's not just about preventing damage; it's about giving you peace of mind.
- **What does the Battery Give You?**
  - **Mobility:** Liberates you from the constraints of power cords, giving you the freedom to work in remote or hard-to-reach locations.
  - **Efficiency:** No more time wasted searching for power outlets or running extension cords. Just efficient uninterrupted work for 3+ hours.
  - **Safety:** By eliminating the need for power cords, there is less risk of trips and falls.
  - Conveniently charge battery even during use.
  - No need for a transformer in the UK.

Technical Specifications	
Pipe Size Ranges	
Cleaning	DN32-75
Cutting	DN32-75
Coating	DN32-75
Shaft	
Usable Length	16m
Shaft Size	8mm
Casing Type	Flexible
Speed (RPM)	550-2200 (stepless speed control)
Power	UK/US: 110/120V, 15 Amp EU: 220/230V, 16 Amp
Weight	33kg w/o battery
Battery Weight	Standard: 3.5kg High Output: 4.1kg
Size	740x519x404mm
Safety	Protective outer shaft casing, operator presence foot control, electric clutch, & E-stop.

\* High Output Battery upgrade sold separately.

\*\* Small Diameter DN32-40 tooling package

## More Info/Guides/Technical Support:

- Visit [picoteinstitute.com](http://picoteinstitute.com) for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Battery Powered Mini Cleaner Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

## PRODUCTS AND SPARE PARTS

Battery Super Mini Cleaner Products & Parts	
PN	Description
3540002816	Battery Super Mini Cleaner EU (Includes Cleaning tools package: DN32-40)
3540002816UK	Battery Super Mini Cleaner UK (Includes Cleaning tools package: DN32-40)
3540002816US	Super Mini Cleaner (Battery) US (Includes Cleaning tools package: 1¼-1½")
3540002818US	Super Mini Cleaner (Battery) US (Includes Cutting tools package: 1¼-1½")
Spare Parts	
9540004011	Standard Battery
9540004035	High Output Battery
9540004013EU	Spare Charger for EU
9540004013UK	Spare Charger for UK
9540004013US	Spare Charger for US
131203108517	Mini Cleaner Replacement Shaft with Flexible Casing (16.5m)
9311713099	Mini Cleaner Shaft Spring Casing only (16.5m)
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 litres)
1350000021	Picote Flexible Shaft Lubricant (package of 6 bottles)

+C Camera version or upgrade available.

