

SUPER MINI MILLER (BATTERY)

Powerful, Efficient, Mobile, & Eco-Friendly



The Picote Mini Miller has long been a trusted name synonymous with reliability, efficiency, and power. While the new Super Mini Miller (Battery) version does run off a long-lasting battery, it's much more than just a battery-powered version of its predecessor. It is loaded with new features like an electronic clutch, stepless speed control, and a dedicated motor to make it more powerful, efficient, mobile, and eco-friendly.

It makes quick work of cleaning, descaling, and removing roots in 2-4" pipes and for reinstatements in 2-3" pipe. Pair it with the Picote Mini Coating Pump for coating in 2-6" pipes as well.

USES AND BENEFITS

- **Flexible:** Navigates 90° bends.
- **High Speed/High Torque:** 550-2200 rpm.
- **Dedicated Motor:** Optimized for increased power matched with better clutch engagement precision to create perfectly balanced performance.
- **Stepless Speed Control:** Seamless speed adjustment whether you need raw power for stubborn blockages or finesse for delicate operations, control is at your fingertips.
- **Electronic Clutch:** Safety meets convenience with the electronic safety clutch. Automatically disengages the drive if you encounter resistance beyond its set limit. It's not just about preventing damage; it's about giving you peace of mind.
- **What does the Battery Give You?**
 - **Mobility:** Liberates you from the constraints of power cords, giving you the freedom to work in remote or hard-to-reach locations.
 - **Efficiency:** No more time wasted searching for power outlets or running extension cords. Just efficient uninterrupted work for 3+ hours.
 - **Safety:** By eliminating the need for power cords, there is less risk of trips and falls.
 - Conveniently charge battery even during use.
- +C Camera version or upgrade available.

Technical Specifications

Technical Specifications	
Pipe Size Ranges	
Cleaning	2-4"
Cutting	2-3"
Coating	2-6"
Shaft	
Usable Length	50' (optional 32' extension)
Shaft Size	1/3"
Casing Type	Thick
Speed (RPM)	550-2200 (stepless speed control)
Power	US/UK: 120/110V, 15 Amp
Weight	73 lbs w/o battery
Battery Weight	Standard Output: 7.7 lbs High Output: 9.0 lbs*
Size	29x20x16"
Safety	Protective outer shaft casing, operator presence foot control, electric clutch, & E-stop.

**High Output Battery upgrade sold separately.*

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Safety & Operations Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Super Mini Miller (Battery) Products & Parts	
PN	Description
3540002817US	Super Mini Miller (Battery) US
3540002817EU	Battery Super Mini Miller EU
3540002817UK	Battery Super Mini Miller UK
Spare Parts	
9540004011	Standard Battery
9540004035	High Output Battery
9540004013US	Spare Charger for US
9540004013EU	Spare Charger for EU
9540004013UK	Spare Charger for UK
131203108517	Mini Cleaner Replacement Shaft with Flexible Casing (54')
9311713099	Mini Cleaner Shaft Spring Casing only (54')
1350000020	Picote Flexible Shaft Lubricant (bottle: 17oz)
1350000021	Picote Flexible Shaft Lubricant (package of 6 bottles)

